



Stainless Steel Roofing Nails (Slating Nails) Ring Barb

PROUDLY SERVICING CONTRACTORS AND BUILDERS FOR OVER 150 YEARS



- **Best Choice for:** Installation of asphalt and architectural shingles
- **Best Choice for:** Installation of cedar roof shingles
- **Best Choice for:** Maximum corrosion resistance in harsh environmental conditions

Penny Size	Length (in.)	Gauge	Head Dia. (in.)	Shank Type	Shank Dia. (In.)	Alloy	Approx. Count/Lbs.	1 lb. Part#	5 lb. Part#	25 lb. Part#	50 lb. Part#
1d	3/4	10	3/8	Ring Barb	0.134	T-304	275	5R****	5R****	5R1004	5R1006
2d	1	10	3/8	Ring Barb	0.134	T-304	207	5R2107	5R2111	5R2110	5R2105
3d	1 1/4	10	3/8	Ring Barb	0.134	T-304	171	5R3107	5R3106	5R3108	5R3105
4d	1 1/2	10	3/8	Ring Barb	0.134	T-304	149	5R4197	5R4155	5R4151	5R4150
5d	1 3/4	10	3/8	Ring Barb	0.134	T-304	131	5R2129	5R2128	5R2127	5R2126
6d	2	10	3/8	Ring Barb	0.134	T-304	117	5R4209	5R4207	5R4219	5R4204
8d	2 1/2	10	3/8	Ring Barb	0.134	T-304	94	5R1062	5R1063	5R1064	5R1065
10d	3	10	3/8	Ring Barb	0.134	T-304	78	5R4217	5R4218	5R4216	5R4202
16d	3 1/2	10	3/8	Ring Barb	0.134	T-304	70	5R****	5R****	5R****	5R1072

T-316 – Please Call Sales Team for Product Codes

Other sizes available

*****Available upon request*

- Corrosion Resistant, Durable, Attractive
- Manufactured from T-304 and T-316 Stainless Steel
- Ring barb shanks offer greater holding power in extreme weather climates
- Available with or without rubber washers
- Manufactured with large slating heads & Diamond points
- Also available in smooth shanks