



# Stainless Steel Common Nails Ring Barb

**PROUDLY SERVICING CONTRACTORS AND BUILDERS FOR OVER 150 YEARS**

- **Best Choice for:** Permanent framing and general construction
- **Best Choice for:** Installation of residential and commercial decks and docks
- **Best Choice for:** Marine applications where maximum corrosion resistance is needed for harsh environmental conditions



Penny Size	Length (in.)	Gauge	Head Dia. (in.)	Shank Type	Shank Dia. (in.)	Alloy	Approx. Count/Lbs.	1 lb. Part#	5 lb. Part#	25 lb. Part#	50 lb. Part#
1d	3/4	14	13/64	Ring Barb	0.083	T-304	757	5G****	5G****	5G****	5G1112
2d	1	15	11/64	Ring Barb	0.720	T-304	807	5G1110	5G****	5G****	5G1106
3d	1 1/4	14	13/64	Ring Barb	0.083	T-304	473	5G****	5G****	5G1103	5G1095
4d	1 1/2	14	13/64	Ring Barb	0.083	T-304	413	5G1099	5G****	5G****	5G1096
4d	1 1/2	12	1/4	Ring Barb	0.109	T-304	228	5G1088	5G****	5G2084	5G1085
5d	1 3/4	12	1/4	Ring Barb	0.109	T-304	182	5G1081	5G****	5G****	5G****
6d	2	11	17/64	Ring Barb	0.120	T-304	144	5G****	5G****	5G1078	5G1075
7d	2 1/4	9	5/16	Ring Barb	0.148	T-304	80	5G****	5G****	5G****	5G****
8d	2 1/2	10	9/32	Ring Barb	0.134	T-304	94	5G1066	5G****	5G1142	5G1065
9d	2 3/4	10	9/32	Ring Barb	0.134	T-304	80	5G****	5G****	5G****	5G****
10d	3	9	5/16	Ring Barb	0.148	T-304	67	5G1058	5G****	5G1057	5G1055
12d	3 1/4	9	5/16	Ring Barb	0.148	T-304	57	5G****	5G****	5G****	5G1028
16d	3 1/2	8	11/32	Ring Barb	0.165	T-304	44	5G****	5G****	5G1021	5G1025
20d	4	8	11/32	Ring Barb	0.165	T-304	41	5G****	5G****	5G****	5G1049
20d	4	6	13/32	Ring Barb	0.203	T-304	25	5G1013	5G****	5G1004	5G1015
40d	5	6	13/32	Ring Barb	0.203	T-304	19	5G****	5G****	5G1003	5G1005

**T-316 – Please Call Sales Team for Product Codes**

*Other sizes available*

*\*\*\*\*Available upon request*

- Corrosion resistant, durable, and attractive
- Manufactured from T-304 and T-316 Stainless Steel
- Ring barb shanks offer greater holding power in extreme weather climates
- Manufactured with diamond points for easy driving
- Also available in smooth shanks