


Stainless Steel Common Nails Smooth Shank

PROUDLY SERVICING CONTRACTORS AND BUILDERS FOR OVER 150 YEARS



- **Best Choice for:** Permanent framing and general construction
- **Best Choice for:** Installation of residential and commercial decks and docks
- **Best Choice for:** Marine applications where maximum corrosion resistance is needed for harsh environmental conditions

Penny Size	Length (in.)	Gauge	Head Dia. (in.)	Shank Type	Shank Dia. (In.)	Alloy	Approx. Count/Lbs.	1 lb. Part#	5 lb. Part#	25 lb. Part#	50 lb. Part#
3d	1 1/4	14	13/64	Smooth	0.083	T-304	473	5E1111	5E****	5E****	5E1110
4d	1 1/2	12	1/4	Smooth	0.109	T-304	228	5E1081	5E****	5E1082	5E1080
5d	1 3/4	12	1/4	Smooth	0.109	T-304	193	5E****	5E****	5E****	5E1075
6d	2	11	17/64	Smooth	0.120	T-304	144	5E1068	5E****	5E****	5E1070
8d	2 1/2	10	9/32	Smooth	0.134	T-304	94	5E1062	5E1061	5E1063	5E1060
9d	2 3/4	10	9/32	Smooth	0.134	T-304	80	5E****	5E****	5E****	5E1064
10d	3	9	5/16	Smooth	0.148	T-304	67	5E1052	5E1051	5E****	5E1050
16d	3 1/2	8	11/32	Smooth	0.165	T-304	44	5E1044	5E5040	5E****	5E1040
20d	4	8	11/32	Smooth	0.165	T-304	41	5E****	5E****	5E****	5E1045
20d	4	6	13/32	Smooth	0.203	T-304	25	5E1029	5E1031	5E****	5E1030

T-316 – Please Call Sales Team for Product Codes

Other sizes available

*****Available upon request*

- Corrosion resistant, durable, and attractive
- Manufactured from T-304 and T-316 Stainless Steel
- Ring barb shanks offer greater holding power in extreme weather climates
- Manufactured with diamond points for easy driving
- Also available in smooth shanks