



Copper Roofing Nails (Slating Nails) Ring Barb

PROUDLY SERVICING CONTRACTORS AND BUILDERS FOR OVER 150 YEARS

Copper Roofing Nails (Slating Nails) Ring Barb

- **Best Choice for:** Installation of Slate, Tile and Copper Roofing
- **Best Choice for:** Installation of Copper Flashing and Hardware
- **Best Choice for:** Long term corrosion resistance in harsh environments



Penny Size	Length (in.)	Gauge	Head Dia. (in.)	Shank Dia. (In.)	Approx. Count/Lbs.	1 lb. Part#	5 lb. Part#	25 lb. Part#	50 lb. Part#
1d	3/4	11	3/8	0.120	289	3K****	3K0378	3K0377	3K0379
2d	1	11	3/8	0.120	240	3K0385	3K0384	3K0382	3K0380
3d	1 1/4	10	27/64	0.134	176	3K0453	3K0455	3K0452	3K0450
3d	1 1/4	11	3/8	0.120	219	3K0393	3K0392	3K0396	3K0390
4d	1 1/2	10	27/64	0.134	146	3K0466	3K0464	3K0461	3K0460
4d	1 1/2	11	3/8	0.120	183	3K0401	3K0402	3K0403	3K0400
5d	1 3/4	10	27/64	0.134	125	3K0476	3K0475	3K0472	3K0470
5d	1 3/4	11	3/8	0.120	156	3K0411	3K0415	3K0412	3K0410
6d	2	10	27/64	0.134	110	3K****	3K0482	3K0481	3K0480
6d	2	11	3/8	0.120	137	3K0421	3K****	3K0425	3K0420
8d	2 1/2	10	27/64	0.134	88	3K0488	3K0489	3K0487	3K0490
10d	3	10	27/64	0.134	68	3K0054	3K0055	3K0049	3K0050

Other sizes available

****Available upon request

- Produced with top quality CDA-110 Copper in conformance with ASTM B49
- Ring barb shanks offer greater holding power for extreme weather climates
- Shank Diameters fit pre-formed tile and Slate holes
- Larger head diameters preferred for covering the tile holes and installing copper flashing and vents
- Manufactured with Diamond points for easy driving
- Also available in smooth shanks